

Lp.	Ilość skrzydeł	Wymiary otworu w świetle (cm x cm)	Powierzchnia geometryczna (m <sup>2</sup> )	Podstawa 35 cm pow. czynna oddymiania (Aa m <sup>2</sup> )	Podstawa 50 cm pow. czynna oddymiania (Aa m <sup>2</sup> )	Typ siłownika
1	1	100 x 100	1,00	0,63	0,68	D+H ZA 155/800-HS
2	1	110 x 110	1,21	0,77	0,81	D+H ZA 155/800-HS
3	1	120 x 120	1,44	0,92	0,96	D+H ZA 155/800-HS
4	1	130 x 130	1,69	1,10	1,13	D+H ZA 155/1000-HS
5	1	140 x 140	1,96	1,27	1,31	D+H ZA 155/1000-HS
6	1	100 x 110	1,10	0,69	0,74	D+H ZA 155/800-HS
7	1	100 x 120	1,20	0,77	0,80	D+H ZA 155/800-HS
8	1	100 x 130	1,30	0,83	0,87	D+H ZA 155/800-HS
9	1	100 x 140	1,40	0,90	0,94	D+H ZA 155/800-HS
10	1	100 x 150	1,50	0,96	1,01	D+H ZA 155/800-HS
11	1	100 x 160	1,60	1,02	1,07	D+H ZA 155/800-HS
12	1	100 x 170	1,70	1,09	1,14	D+H ZA 155/800-HS
13	1	100 x 180	1,80	1,17	1,21	D+H ZA 155/800-HS
14	1	100 x 190	1,90	1,24	1,27	D+H ZA 155/800-HS
15	1	100 x 200	2,00	1,30	1,34	D+H ZA 155/800-BSY+HS Set
16	1	100 x 210	2,10	1,37	1,41	D+H ZA 155/800-BSY+HS Set
17	1	100 x 220	2,20	1,43	1,47	D+H ZA 155/800-BSY+HS Set
18	1	100 x 230	2,30	1,50	1,54	D+H ZA 155/800-BSY+HS Set
19	1	100 x 240	2,40	1,56	1,61	D+H ZA 155/800-BSY+HS Set
20	1	100 x 250	2,50	1,63	1,68	D+H ZA 155/800-BSY+HS Set
21	1	110 x 120	1,32	0,84	0,88	D+H ZA 155/800-HS
22	1	110 x 130	1,43	0,92	0,96	D+H ZA 155/800-HS
23	1	110 x 140	1,54	0,99	1,03	D+H ZA 155/800-HS
24	1	110 x 150	1,49	1,06	1,11	D+H ZA 155/800-HS
25	1	110 x 160	1,76	1,14	1,18	D+H ZA 155/800-HS
26	1	110 x 170	1,87	1,22	1,25	D+H ZA 155/800-HS
27	1	110 x 180	1,98	1,29	1,33	D+H ZA 155/800-HS
28	1	110 x 190	2,09	1,36	1,40	D+H ZA 155/800-BSY+HS Set
29	1	110 x 200	2,20	1,43	1,47	D+H ZA 155/800-BSY+HS Set
30	1	110 x 210	2,10	1,50	1,55	D+H ZA 155/800-BSY+HS Set
31	1	110 x 220	2,42	1,57	1,62	D+H ZA 155/800-BSY+HS Set
32	1	110 x 230	2,53	1,64	1,67	D+H ZA 155/800-BSY+HS Set
33	1	110 x 240	2,64	1,72	1,74	D+H ZA 155/800-BSY+HS Set
34	1	110 x 250	2,75	1,79	1,82	D+H ZA 155/800-BSY+HS Set
35	1	120 x 130	1,56	1,00	1,05	D+H ZA 155/800-HS
36	1	120 x 140	1,68	1,09	1,13	D+H ZA 155/800-HS
37	1	120 x 150	1,80	1,17	1,21	D+H ZA 155/800-HS
38	1	120 x 160	1,92	1,25	1,29	D+H ZA 155/800-HS
39	1	120 x 170	2,04	1,33	1,37	D+H ZA 155/800-BSY+HS Set
40	1	120 x 180	2,16	1,40	1,45	D+H ZA 155/800-BSY+HS Set
41	1	120 x 190	2,28	1,48	1,53	D+H ZA 155/800-BSY+HS Set
42	1	120 x 200	2,40	1,56	1,58	D+H ZA 155/800-BSY+HS Set
43	1	120 x 210	2,41	1,64	1,66	D+H ZA 155/800-BSY+HS Set

Lp.	Ilość skrzydeł	Wymiary otworu w świetle (cm x cm)	Powierzchnia geometryczna (m <sup>2</sup> )	Podstawa 35 cm pow. czynna oddymiania (Aa m <sup>2</sup> )	Podstawa 50 cm pow. czynna oddymiania (Aa m <sup>2</sup> )	Typ siłownika
44	1	120 x 220	2,64	1,72	1,74	D+H ZA 155/800-BSY+HS Set
45	1	120 x 230	2,76	1,79	1,82	D+H ZA 155/800-BSY+HS Set
46	1	120 x 240	2,88	1,87	1,90	D+H ZA 155/800-BSY+HS Set
47	1	120 x 250	3,00	1,95	1,98	D+H ZA 155/800-BSY+HS Set
48	1	130 x 140	1,82	1,18	1,22	D+H ZA 155/1000-HS
49	1	130 x 150	1,95	1,27	1,31	D+H ZA 155/1000-HS
50	1	130 x 160	2,08	1,35	1,39	D+H ZA 155/1000-BSY+HS Set
51	1	130 x 170	2,21	1,44	1,48	D+H ZA 155/1000-BSY+HS Set
52	1	130 x 180	2,34	1,52	1,54	D+H ZA 155/1000-BSY+HS Set
53	1	130 x 190	2,47	1,61	1,63	D+H ZA 155/1000-BSY+HS Set
54	1	130 x 200	2,60	1,69	1,72	D+H ZA 155/1000-BSY+HS Set
55	1	130 x 210	2,73	1,77	1,80	D+H ZA 155/1000-BSY+HS Set
56	1	130 x 220	2,86	1,89	1,89	D+H ZA 155/1000-BSY+HS Set
57	1	130 x 230	2,99	1,97	1,97	D+H ZA 155/1000-BSY+HS Set
58	1	130 x 240	3,12	2,06	2,06	D+H ZA 155/1000-BSY+HS Set
59	1	130 x 250	3,25	2,15	2,15	D+H ZA 155/1000-BSY+HS Set
60	1	140 x 150	2,10	1,37	1,41	D+H ZA 155/1000-BSY+HS Set
61	1	140 x 160	2,24	1,46	1,48	D+H ZA 155/1000-BSY+HS Set
62	1	140 x 170	2,38	1,55	1,57	D+H ZA 155/1000-BSY+HS Set
63	1	140 x 180	2,52	1,64	1,66	D+H ZA 155/1000-BSY+HS Set
64	1	140 x 190	2,66	1,73	1,76	D+H ZA 155/1000-BSY+HS Set
65	1	140 x 200	2,80	1,85	1,85	D+H ZA 155/1000-BSY+HS Set
66	1	140 x 210	2,94	1,94	1,94	D+H ZA 155/1000-BSY+HS Set
67	1	140 x 220	3,08	2,03	2,03	D+H ZA 155/1000-BSY+HS Set
68	1	140 x 230	3,22	2,13	2,13	D+H ZA 155/1000-BSY+HS Set
69	1	140 x 240	3,36	2,22	2,22	D+H ZA 155/1000-BSY+HS Set
70	1	140 x 250	3,50	2,31	2,31	D+H ZA 155/1000-BSY+HS Set
71	2	150 x 150	2,25	1,31	1,37	D+H ZA 155/600-BSY+HS Set
72	2	150 x 160	2,40	1,42	1,46	D+H ZA 155/600-BSY+HS Set
73	2	150 x 170	2,55	1,50	1,56	D+H ZA 155/600-BSY+HS Set
74	2	150 x 180	2,70	1,59	1,67	D+H ZA 155/600-BSY+HS Set
75	2	150 x 190	2,85	1,71	1,77	D+H ZA 155/600-BSY+HS Set
76	2	150 x 200	3,00	1,80	1,86	D+H ZA 155/600-BSY+HS Set
77	2	150 x 210	3,15	1,89	1,98	D+H ZA 155/600-BSY+HS Set
78	2	150 x 220	3,30	1,98	2,08	D+H ZA 155/600-BSY+HS Set
79	2	150 x 230	3,45	2,10	2,17	D+H ZA 155/600-BSY+HS Set
80	2	150 x 240	3,60	2,20	2,27	D+H ZA 155/600-BSY+HS Set
81	2	150 x 250	3,75	2,29	2,40	D+H ZA 155/600-BSY+HS Set
82	2	150 x 260	3,90	2,38	2,50	D+H ZA 155/600-BSY+HS Set
83	2	150 x 270	4,05	2,47	2,59	D+H ZA 155/600-BSY+HS Set
84	2	150 x 280	4,20	2,60	2,69	D+H ZA 155/600-BSY+HS Set
85	2	150 x 290	4,35	2,70	2,78	D+H ZA 155/600-BSY+HS Set
86	2	150 x 300	4,50	2,79	2,88	D+H ZA 155/600-BSY+HS Set

Lp.	Ilość skrzydeł	Wymiary otworu w świetle (cm x cm)	Powierzchnia geometryczna (m <sup>2</sup> )	Podstawa 35 cm pow. czynna oddymiania (Aa m <sup>2</sup> )	Podstawa 50 cm pow. czynna oddymiania (Aa m <sup>2</sup> )	Typ siłownika
87	2	160 x 160	2,56	1,51	1,59	D+H ZA 155/600-BSY+HS Set
88	2	160 x 170	2,72	1,60	1,69	D+H ZA 155/600-BSY+HS Set
89	2	160 x 180	2,88	1,73	1,79	D+H ZA 155/600-BSY+HS Set
90	2	160 x 190	3,04	1,82	1,92	D+H ZA 155/600-BSY+HS Set
91	2	160 x 200	3,20	1,92	2,02	D+H ZA 155/600-BSY+HS Set
92	2	160 x 210	3,36	2,05	2,12	D+H ZA 155/600-BSY+HS Set
93	2	160 x 220	3,52	2,15	2,22	D+H ZA 155/600-BSY+HS Set
94	2	160 x 230	3,68	2,24	2,36	D+H ZA 155/600-BSY+HS Set
95	2	160 x 240	3,84	2,34	2,46	D+H ZA 155/600-BSY+HS Set
96	2	160 x 250	4,00	2,48	2,56	D+H ZA 155/600-BSY+HS Set
97	2	160 x 260	4,16	2,58	2,66	D+H ZA 155/600-BSY+HS Set
98	2	160 x 270	4,32	2,68	2,76	D+H ZA 155/600-BSY+HS Set
99	2	160 x 280	4,48	2,78	2,87	D+H ZA 155/600-BSY+HS Set
100	2	160 x 290	4,64	2,88	3,02	D+H ZA 155/600-BSY+HS Set
101	2	160 x 300	4,80	2,98	3,12	D+H ZA 155/600-BSY+HS Set
102	2	170 x 170	2,89	1,73	1,79	D+H ZA 155/600-BSY+HS Set
103	2	170 x 180	3,06	1,84	1,93	D+H ZA 155/600-BSY+HS Set
104	2	170 x 190	3,23	1,97	2,03	D+H ZA 155/600-BSY+HS Set
105	2	170 x 200	3,40	2,07	2,14	D+H ZA 155/600-BSY+HS Set
106	2	170 x 210	3,57	2,18	2,28	D+H ZA 155/600-BSY+HS Set
107	2	170 x 220	3,74	2,28	2,39	D+H ZA 155/600-BSY+HS Set
108	2	170 x 230	3,91	2,42	2,50	D+H ZA 155/600-BSY+HS Set
109	2	170 x 240	4,08	2,53	2,61	D+H ZA 155/600-BSY+HS Set
110	2	170 x 250	4,25	2,64	2,72	D+H ZA 155/600-BSY+HS Set
111	2	170 x 260	4,42	2,74	2,87	D+H ZA 155/600-BSY+HS Set
112	2	170 x 270	4,59	2,85	2,98	D+H ZA 155/600-BSY+HS Set
113	2	170 x 280	4,76	2,95	3,09	D+H ZA 155/600-BSY+HS Set
114	2	170 x 290	4,93	3,11	3,20	D+H ZA 155/600-BSY+HS Set
115	2	170 x 300	5,10	3,21	3,32	D+H ZA 155/600-BSY+HS Set
116	2	180 x 180	3,24	1,98	2,04	D+H ZA 155/800-BSY+HS Set
117	2	180 x 190	3,42	2,09	2,15	D+H ZA 155/800-BSY+HS Set
118	2	180 x 200	3,60	2,20	2,30	D+H ZA 155/800-BSY+HS Set
119	2	180 x 210	3,78	2,31	2,42	D+H ZA 155/800-BSY+HS Set
120	2	180 x 220	3,96	2,46	2,53	D+H ZA 155/800-BSY+HS Set
121	2	180 x 230	4,14	2,57	2,65	D+H ZA 155/800-BSY+HS Set
122	2	180 x 240	4,32	2,68	2,81	D+H ZA 155/800-BSY+HS Set
123	2	180 x 250	4,50	2,79	2,93	D+H ZA 155/800-BSY+HS Set
124	2	180 x 260	4,68	2,90	3,04	D+H ZA 155/800-BSY+HS Set
125	2	180 x 270	4,86	3,06	3,16	D+H ZA 155/800-BSY+HS Set
126	2	180 x 280	5,04	3,18	3,28	D+H ZA 155/800-BSY+HS Set
127	2	180 x 290	5,22	3,29	3,39	D+H ZA 155/800-BSY+HS Set
128	2	180 x 300	5,40	3,40	3,51	D+H ZA 155/800-BSY+HS Set
129	2	190 x 190	3,61	2,20	2,31	D+H ZA 155/800-BSY+HS Set

Lp.	Ilość skrzydeł	Wymiary otworu w świetle (cm x cm)	Powierzchnia geometryczna (m <sup>2</sup> )	Podstawa 35 cm pow. czynna oddymiania (Aa m <sup>2</sup> )	Podstawa 50 cm pow. czynna oddymiania (Aa m <sup>2</sup> )	Typ siłownika
130	2	190 x 200	3,80	2,36	2,43	D+H ZA 155/800-BSY+HS Set
131	2	190 x 210	3,99	2,47	2,55	D+H ZA 155/800-BSY+HS Set
132	2	190 x 220	4,18	2,59	2,68	D+H ZA 155/800-BSY+HS Set
133	2	190 x 230	4,37	2,71	2,84	D+H ZA 155/800-BSY+HS Set
134	2	190 x 240	4,56	2,83	2,96	D+H ZA 155/800-BSY+HS Set
135	2	190 x 250	4,75	2,99	3,09	D+H ZA 155/800-BSY+HS Set
136	2	190 x 260	4,94	3,11	3,21	D+H ZA 155/800-BSY+HS Set
137	2	190 x 270	5,13	3,23	3,33	D+H ZA 155/800-BSY+HS Set
138	2	190 x 280	5,32	3,35	3,46	D+H ZA 155/800-BSY+HS Set
139	2	190 x 290	5,51	3,47	3,64	D+H ZA 155/800-BSY+HS Set
140	2	190 x 300	5,70	3,59	3,76	D+H ZA 155/800-BSY+HS Set
141	2	200 x 200	4,00	2,48	2,56	D+H ZA 155/800-BSY+HS Set
142	2	200 x 210	4,20	2,60	2,69	D+H ZA 155/800-BSY+HS Set
143	2	200 x 220	4,40	2,73	2,86	D+H ZA 155/800-BSY+HS Set
144	2	200 x 230	4,60	2,90	2,99	D+H ZA 155/800-BSY+HS Set
145	2	200 x 240	4,80	3,02	3,12	D+H ZA 155/800-BSY+HS Set
146	2	200 x 250	5,00	3,15	3,25	D+H ZA 155/800-BSY+HS Set
147	2	200 x 260	5,20	3,28	3,38	D+H ZA 155/800-BSY+HS Set
148	2	200 x 270	5,40	3,40	3,56	D+H ZA 155/800-BSY+HS Set
149	2	200 x 280	5,60	3,53	3,70	D+H ZA 155/800-BSY+HS Set
150	2	200 x 290	5,80	3,71	3,83	D+H ZA 155/800-BSY+HS Set
151	2	200 x 300	6,00	3,84	3,96	D+H ZA 155/800-BSY+HS Set
152	2	220 x 220	4,84	3,05	3,15	D+H ZA 155/800-BSY+HS Set
153	2	220 x 240	5,28	3,33	3,48	D+H ZA 155/800-BSY+HS Set
154	2	220 x 260	5,72	3,66	3,78	D+H ZA 155/800-BSY+HS Set
155	2	220 x 280	6,16	3,94	4,07	D+H ZA 155/800-BSY+HS Set
156	2	220 x 300	6,60	4,22	4,42	D+H ZA 155/800-BSY+HS Set
157	2	240 x 240	5,76	3,69	3,80	D+H ZA 155/1000-BSY+HS Set
158	2	240 x 260	6,24	3,99	4,12	D+H ZA 155/1000-BSY+HS Set
159	2	240 x 280	7,20	4,30	4,50	D+H ZA 155/1000-BSY+HS Set
160	2	240 x 300	7,20	4,68	4,82	D+H ZA 155/1000-BSY+HS Set
161	2	260 x 260	6,76	4,33	4,53	D+H ZA 155/1000-BSY+HS Set
162	2	260 x 280	7,28	4,73	4,88	D+H ZA 155/1000-BSY+HS Set
163	2	260 x 300	7,80	5,07	5,23	D+H ZA 155/1000-BSY+HS Set
164	2	280 x 280	7,84	5,10	5,25	D+H ZA 155/1000-BSY+HS Set
165	2	280 x 300	8,40	5,46	5,71	D+H ZA 155/1000-BSY+HS Set
166	2	250 x 250	6,25	4,00	4,13	D+H ZA 155/1000-BSY+HS Set
167	2	250 x 300	7,50	4,88	5,03	D+H ZA 155/1000-BSY+HS Set
168	2	300 x 300	9,00	5,94	6,12	D+H ZA 155/1000-BSY+HS Set